

# Vacuum Sealer with Nozzle

## 外抽吸嘴式真空封口機

- Stainless steel retractable Nozzle. • 封口線：5 mm
- Oil-less pump. • 可抽氣液體，粉末
- Stainless steel retractable Nozzle. • Oil-less pump.

Model NO.	型號	ASV-320
Voltage	電壓	AC100V-240V 1 phase
Power(Watt.)	消費電力	Watt.: 200 W
Vac. Capacity	真空能力	-80 Kpa
Max. sealing	最大封口	5 mm x 300 mm
Vacuum degree	真空度	>70%
Dimension	機器尺寸	394 x 266 x 175.3 (mm)
Weight	機台重量	4.35 KG



- 封口線：5 mm
- 可抽氣液體，粉末
- Stainless Steel housing
- with a Canister.

Model NO.	型號	WZV-305
Voltage	電壓	120V/220V
Power(Watt.)	電力	1100W / 9.9A
Max. Sealing	最大封口	300 x 5 mm
Vacuum Time	真空時間	0-99 sec.
Sealing Time	封口時間	0-6.0 sec.
Cooling Time	壓凝時間	0-9 sec.
Weight	機台重量	15.6 KGS
Dimensions	尺寸	502 x 298 x 162 cm

- Extra Air Compressor 6-7kg/cm<sup>2</sup> 要有空壓機
- Can be installed Gas flushing 可加充氣設備：
- Oil-less pump
- Double-sides sealing: 5 mm, 10 mm
- Any vacuumable bags: 適用袋型：PE 尼龍條紋袋、尼龍摺邊袋、鋁箔摺邊袋、尼龍 / 鋁箔合掌袋
- Optional: Stainless steel housing, Oil-Filling pump, Vacuum ejector, Date coder.

Model NO.	VV-305T VV-3010T	VV-455T VV-4510T	VV-605T VV-6010T	VV-755T
Voltage	AC 110V / 220V 1 phase			
Max. Sealing	5 x 310 mm	5 x 460 mm	5 x 610 mm	5 x 755 mm
Vacuum Cap. (Made in Italy)	20 L/min	20 L/min	30 L/min	30 L/min
Pump Cap.	180 Torr	180 Torr	180 Torr	180 Torr
Power	Amp: 10 A Watt.: 1000 W	Amp: 15 A Watt.: 1300 W	Amp: 20 A Watt.: 1760 W	Amp: 25 A Watt.: 2750 W
Working Table	300 mm x 250 mm	450 mm x 450 mm	600 mm x 600 mm	750 mm x 600 mm
Dimensions	460 x 690 x 330 mm	475 x 820 x 330 mm	665 x 970 x 330 mm	815 x 970 x 330 mm
Air Compressor	(customer prepared) 6-7 Kgs/cm <sup>2</sup>			

Table-Top



Model NO.	型號	VVB-8010T 鋁箔、錫箔袋	VVB-10010T 鋁箔、錫箔袋
Voltage	電壓	AC 220V 1 phase	
Power	電力	Amp: 15 A Watt.: 11 KW	Amp: 15 A Watt.: 12 KW
Max. Sealing	最大封口	10 x 810 mm	10 x 1010 mm
Vacuum Cap.	抽氣能力	DP-120 (300 W)	DP-120 (300 W)
Working Table	工作板	800 x 400 mm	1000 x 400 mm
Pump Cap.	真空能力	180 Torr	180 Torr
Dimension	機台尺寸	850 x 430 x 1010 mm	1050 x 430 x 1010 mm
Weight	重量	115 KGS	135 KGS
Air Compressor	空壓機	(Customer prepared)	6~7 Kgs/cm <sup>2</sup>

Model NO.	型號	LMV-6010T	LMV-7510T	LMV-9010T
Voltage	電壓	AC 220V 1 phase		
Power	電力	Amp: 20 A Watt.: 7 KW	Amp: 20 A Watt.: 9 KW	Amp: 25 A Watt.: 10 KW
Max. Sealing	最大封口	600 mm x 10 mm x 2	750 mm x 10 mm x 2	900 mm x 10 mm x 2
Sealing Time	封口時間		0.0 - 3.0 Sec.	
Vacuum Time	抽氣時間		01 - 90 Sec.	
Cooling Time	冷卻時間		0 - 10 Sec.	
Pump Capacity	抽氣能力	DP-120 120 liter/min.		
Pump	幫浦	Dry & solid goods Packing (no liquid, powder)		
Weight	重量	Approx. 120 KG	Approx. 130 KG	Approx. 150 KG
Dimension	尺寸	750 x 600 x 1620 mm	900 x 600 x 1620 mm	1050 x 600 x 1620 mm
Compressor needed	空壓機	6-7 KGS/cm <sup>2</sup>		
Remarks	備註	1. Electrostatic painted housing 2. The height of head parts can be adjusted. 70-110 cm		
Material Used	使用材質	Alum. Foil, Thicker PE Bag		

例如：電子產品、食品、咖啡豆、茶葉、中藥材、水果...



06-2019



# Out of Chamber - Vacuum Sealer

## ~ Commercial grade

適用袋型：尼龍條紋袋、尼龍摺邊袋、鋁箔摺邊袋、尼龍 / 鋁箔合掌袋

- Mini Non- Nozzle Vacuum Sealer is made in Stainless construction. Keeps fresh and preserves longer without freezer. Store clothing scent-free. Commercial-Grade Vacuum Sealer with an extra large Teflon Bar for sealing bags up to 300~400mm, Double piston vacuum-pump, can preserve foods 5-6 times longer than traditional methods. Easy to use, bright LED lights let you monitor the stages of the sealing. Equipped with a see-thru acrylic vacuum lid for perfect bag alignment while sealing. It also equipped with a cooling fan for cooling down the heating inside of machine. Ideal for dry & solid goods packing. It can depend on the bags width to vacuum some bags once to increase the packing efficiency.

### Features:

1. Sealing width: 5mm
2. See - thru upper lid (patented)
3. Suitable for special bag. (refer to Page 2)
4. Ideal for dry and solid goods, less liquid & powder is available.

### SPECIFICATION 規格:

Model NO.	型號	WVM-305	WVM-405	WVM-15
Voltage	電壓	110 / 220 / 240 V		
Power(Watt.)	電力	750 W	935 W	935 W
Max. Sealing	最大封口	300 x 5.0 mm	400 x 5.0mm	400 x 5.0mm
Vacuum Time	真空時間		01-90 sec.	Through Vacuum Sensor
Sealing Time	封口時間	0.0-6.0 sec.		0.0-4.0 sec.
Cooling Time	壓凝時間	0-10 sec.		Set up
Weight	機台重量	10 KGS	11 KGS	11 KGS
Dimensions	尺寸	39.5 x 31 x 15 cm	48.5 x 31 x 15 cm	48.5 x 31 x 15 cm
Materials Used	適用袋子	Channelled(Lined) bags, Nylon Gusset bags, Alum. Gusset bag. (尼龍 / 鋁箔摺邊袋, 尼龍條紋袋, 尼龍合掌袋)		Channelled bags 尼龍條紋袋



圓方圓興業股份有限公司  
WU-HSING ELECTRONICS CO., LTD.

TEL: 886-4-22711498 FAX: 886-4-22712806

台中市 41154 太平區大里工業區工業 15 路 10 號  
No.10, Gongye 15<sup>th</sup> Road, Dali Industrial Park, Taiping Dist.,  
Taichung, Taiwan  
Http://www.wuhsing.com  
E-mail: wuhsing@ms17.hinet.net sealer@wuhsing.com.tw

# Vacuum Sealer with Nozzle

## 外抽吸嘴式真空封口機

- Stainless steel retractable Nozzle. • 封口袋：5 mm
- Oil-less pump. • 可抽氣液體，粉末
- Stainless steel retractable Nozzle. • Oil-less pump.

Model NO.	型號	ASV-320
Voltage	電壓	AC100V-240V 1 phase
Power(Watt.)	消費電力	Watt.: 200 W
Vac. Capacity	真空能力	-80 Kpa
Max. sealing	最大封口	5 mm x 300 mm
Vacuum degree	真空度	>70%
Dimension	機器尺寸	394 x 266 x 175.3 (mm)
Weight	機台重量	4.35 KG



- 封口袋：5 mm
- 可抽氣液體，粉末
- Stainless Steel housing
- with a Canister.

Model NO.	型號	WZV-305
Voltage	電壓	120V/220V
Power(Watt.)	電力	1100W / 9.9A
Max. Sealing	最大封口	300 x 5 mm
Vacuum Time	真空時間	0-99 sec.
Sealing Time	封口時間	0-6.0 sec.
Cooling Time	壓凝時間	0-9 sec.
Weight	機台重量	15.6 KGS
Dimensions	尺寸	502 x 298 x 162 cm

- Extra Air Compressor 6-7kg/cm<sup>2</sup> 要有空壓機
- Can be installed Gas flushing 可加充氣設備：
- Oil-less pump
- Double-sides sealing: 5 mm, 10 mm
- Any vacuumable bags: 適用袋型：PE 尼龍條紋袋、尼龍摺邊袋、鋁箔摺邊袋、尼龍 / 鋁箔合掌袋
- Optional: Stainless steel housing, Oil-Filling pump, Vacuum ejector, Date coder.

Model NO.	VV-305T VV-3010T	VV-455T VV-4510T	VV-605T VV-6010T	VV-755T
Voltage	AC 110V / 220V 1 phase			
Max. Sealing	5 x 310 mm	5 x 460 mm	5 x 610 mm	5 x 755 mm
Vacuum Cap. (Made in Italy)	20 L/min	20 L/min	30 L/min	30 L/min
Pump Cap.	180 Torr	180 Torr	180 Torr	180 Torr
Power	Amp: 10 A Watt.: 1000 W	Amp: 15 A Watt.: 1300 W	Amp: 20 A Watt.: 1760 W	Amp: 25 A Watt.: 2750 W
Working Table	300 mm x 250 mm	450 mm x 450 mm	600 mm x 600 mm	750 mm x 600 mm
Dimensions	460 x 690 x 330 mm	475 x 820 x 330 mm	665 x 970 x 330 mm	815 x 970 x 330 mm
Air Compressor	(customer prepared) 6-7 Kgs/cm <sup>2</sup>			

Table-Top



Model NO.	型號	VVB-8010T 鋁箔、錫箔袋	VVB-10010T 鋁箔、錫箔袋
Voltage	電壓	AC 220V 1 phase	
Power	電力	Amp: 15 A Watt.: 11 KW	Amp: 15 A Watt.: 12 KW
Max. Sealing	最大封口	10 x 810 mm	10 x 1010 mm
Vacuum Cap.	抽氣能力	DP-120 (300 W)	DP-120 (300 W)
Working Table	工作板	800 x 400 mm	1000 x 400 mm
Pump Cap.	真空能力	180 Torr	180 Torr
Dimension	機台尺寸	850 x 430 x 1010 mm	1050 x 430 x 1010 mm
Weight	重量	115 KGS	135 KGS
Air Compressor	空壓機	(Customer prepared)	6~7 Kgs/cm <sup>2</sup>

Model NO.	型號	LMV-6010T	LMV-7510T	LMV-9010T
Voltage	電壓	AC 220V 1 phase		
Power	電力	Amp: 20 A Watt.: 7 KW	Amp: 20 A Watt.: 9 KW	Amp: 25 A Watt.: 10 KW
Max. Sealing	最大封口	600 mm x 10 mm x 2	750 mm x 10 mm x 2	900 mm x 10 mm x 2
Sealing Time	封口時間		0.0 - 3.0 Sec.	
Vacuum Time	抽氣時間		01 - 90 Sec.	
Cooling Time	冷凝時間		0 - 10 Sec.	
Pump Capacity	抽氣能力	DP-120 120 liter/min.		
Pump	幫浦	Dry & solid goods Packing (no liquid, powder)		
Weight	重量	Approx. 120 KG	Approx. 130 KG	Approx. 150 KG
Dimension	尺寸	750 x 600 x 1620 mm	900 x 600 x 1620 mm	1050 x 600 x 1620 mm
Compressor needed	空壓機	6-7 KGS/cm <sup>2</sup>		
Remarks	備註	1. Electrostatic painted housing 2. The height of head parts can be adjusted. 70-110 cm		
Material Used	使用材質	Alum. Foil, Thicker PE Bag		

例如：電子產品、食品、咖啡豆、茶葉、中藥材、水果...



06-2019



# Out of Chamber - Vacuum Sealer

## ~ Commercial grade

適用袋型：尼龍條紋袋、尼龍摺邊袋、鋁箔摺邊袋、尼龍 / 鋁箔合掌袋

• Mini Non- Nozzle Vacuum Sealer is made in Stainless construction. Keeps fresh and preserves longer without freezer. Store clothing scent-free. Commercial-Grade Vacuum Sealer with an extra large Teflon Bar for sealing bags up to 300~400mm, Double piston vacuum-pump, can preserve foods 5-6 times longer than traditional methods. Easy to use, bright LED lights let your monitor the stages of the sealing. Equipped with a see-thru acrylic vacuum lid for perfect bag alignment while sealing. It also equipped with a cooling fan for cooling down the heating inside of machine. Ideal for dry & solid goods packing. It can depend on the bags width to vacuum some bags once to increase the packing efficiency.

### Features:

1. Sealing width: 5mm
2. See - thru upper lid (patented)
3. Suitable for special bag. (refer to Page 2)
4. Ideal for dry and solid goods, less liquid & powder is available.

### SPECIFICATION 規格:

Model NO.	型號	WVM-305	WVM-405	WVM-15
Voltage	電壓	110 / 220 / 240 V		
Power(Watt.)	電力	750 W	935 W	935 W
Max. Sealing	最大封口	300 x 5.0 mm	400 x 5.0mm	400 x 5.0mm
Vacuum Time	真空時間		01-90 sec.	Through Vacuum Sensor
Sealing Time	封口時間	0.0-6.0 sec.		0.0-4.0 sec.
Cooling Time	壓凝時間	0-10 sec.		Set up
Weight	機台重量	10 KGS	11 KGS	11 KGS
Dimensions	尺寸	39.5 x 31 x 15 cm	48.5 x 31 x 15 cm	48.5 x 31 x 15 cm
Materials Used	適用袋子	Channelled(Lined) bags, Nylon Gusset bags, Alum. Gusset bag. (尼龍 / 鋁箔摺邊袋, 尼龍條紋袋, 尼龍合掌袋)		Channelled bags 尼龍條紋袋



圓方圓興業股份有限公司  
WU-HSING ELECTRONICS CO., LTD.  
TEL: 886-4-22711498 FAX: 886-4-22712806

台中市 41154 太平區大里工業區工業 15 路 10 號  
No.10, Gongye 15<sup>th</sup> Road, Dali Industrial Park, Taiping Dist.,  
Taichung, Taiwan  
Http://www.wuhsing.com  
E-mail: wuhsing@ms17.hinet.net sealer@wuhsing.com.tw

# Out of Chamber - Vacuum Sealer – Double-side sealing

## 外抽式真空封口機 - 無袋長限制

通用袋型: 尼龍條紋袋, 尼龍摺邊袋, 鋁箔摺邊袋, 尼龍/鋁箔合掌袋

- Extra Long Vacuum Sealer is metal construction
- Oil-less Pump
- sealing width: 5mm/ 10 mm
- No bag length limited.
- Smaller bags can be vacuum 2-5 bags once.
- Ideal for bigger & Thicker gusset bag (such as Coffee bean bags, Tea leaves bag)

WVV  
Oil-filling pump  
油式幫浦



Model NO.	型號	WVT-455T WVT-605T	WVF-455T WVF-605T	WVB-455T WVB-605T	WVV-605T
Voltage	電壓	110 / 220 / 240 V			
Power(Watt.)	電力	2750 W / 4180 W	2750 W / 4180 W	2750 W / 4180 W	4400 W
Max. Sealing	最大封口	450 x 5.0 mm 600 x 5.0 mm	450 x 5.0 mm 600 x 5.0 mm	450 x 5.0 mm 600 x 5.0 mm	600 x 5.0 mm
Vacuum Time	真空時間	01-90 sec.			
Sealing Time	封口時間	0.0-6.0 sec.			
Cooling Time	壓凝時間	0-10 sec.			
Weight	機台重量	35.5 KGS	42 KGS	63.5 KGS	90 KGS
Dimensions	尺寸	52 x 64.5 x 32 cm	52 x 58 x 92.5 cm	52 x 72 x 87 cm	83 x 65 x 128.5 cm
Materials Used	適用袋子	Thicker Channelled bags, Nylon Gusset bags, Alum. gusset			

Special bags for Out of Chamber Vacuum Sealer



Nylon Channelled (Lined) bag  
尼龍條紋袋  
適用: WVM series



Nylon back fin bag  
尼龍合掌袋  
適用: WVM series



Alum. Back fin bag  
鋁箔合掌袋  
適用: WVM series



Nylon Gusset bag  
適用: WVM, WVT, WVF, WVB, WVV series  
尼龍鋁箔摺角/摺邊袋



smaller & thinner Alum. coffee bag  
薄的鋁箔摺角/摺邊袋  
適用: WVM, WVT, WVF, WVB, WVV series




Big & thicker Alum. Gusset bag  
大而厚的鋁箔摺角/摺邊袋  
適用: WVT, WVF, WVB, WVV

# In -Chamber Vacuum Packer

## 真空槽真空封口機 - 袋子尺寸限制

- Vacuum Chamber size limited.
- Stainless steel housing.
- Suitable bags: Nylon bag, Alum. Bag, Nylon back fin bag.
- Oil-less Pump Ideal for dry and solid goods.
- 真空室尺寸限制
- 不鏽鋼機身
- 乾式PUMP
- 通用乾式、固體物
- 適用袋型: 尼龍袋、鋁箔袋、尼龍/鋁箔合掌袋
- Oil-filling Pump, ideal for less powder or liquid goods.
- 少量液體及粉末之真空包裝



油式PUMP: 1.須加油 2.須清理過濾器

Model NO.	型號	WVVVB-255C	WVVVB-355B
Voltage	電壓	110 / 220 / 240 V	
Chamber Size	真空室尺寸	250 x 330 x 80 mm	370 x 500 x 120 mm
Vacuum Time	真空時間	01-99 sec.	
Sealing Time	封口時間	0.0-3.0 sec.	
Cooling Time	壓凝時間	0-6 sec.	
Weight	機台重量	34 KGS	63 KGS
Dimensions	尺寸	365 x 420 x 360 cm	480 x 560 x 570 cm
Materials Used	適用袋子	Vacuum bag, Alum. Bag, 真空袋, 鋁箔袋	

乾式PUMP-通用乾的固體物

Model NO.	型號	WVVVB-255A	WVVVB-355A
Voltage	電壓	110 / 220 / 240 V	
Chamber Size	真空室尺寸	250 x 330 x 80 mm	370 x 500 x 120 mm
Vacuum Time	真空時間	01-99 sec.	
Sealing Time	封口時間	0.0-3.0 sec.	
Cooling Time	壓凝時間	0-6 sec.	
Weight	機台重量	27 KGS	63 KGS
Dimensions	尺寸	365 x 420 x 360 cm	480 x 560 x 570 cm
Materials Used	適用袋子	Vacuum bag, Alum. Bag, 真空袋, 鋁箔袋	

# Deep Chamber Vacuum Packer- Oil-filling Pump 德製

## 深槽式真空封口機—液體粉末專用

內容物<60%

- 德製油式幫浦 - Oil-Filling PUMP
- 液體、粉末不可超過袋子的60%.
- Liquid or Powder no exceed 60% of bag.
- 例如: 佛跳牆, 人蔘雞, 醬汁, 咖哩粉, 香料...



# Vertical type Vacuum Packing M/C for powder & Liquid

## 站立式槽式真空包裝機 粉末/液體 專用真空機 IN-CHAMBER

- Vertical type 站立式作業, 適合粉末/液體真空作業
- In-Chamber Vacuum 在槽內真空作業, 真空度高
- Touching Control panel 觸控式面板
- 10 Programs 10組記憶功能
- Counting 計數功能
- Powder or Liquid do not exceed 60% of package 粉末/液體勿超過袋裝60%
- Air Compressor: 6-7kg/cm<sup>2</sup> 須外接空壓機



Model	型號	SC-450D
Voltage	電壓	220/240V 1 PH
Sealing width	封口	10 mm (可加第二組封口線)
Chamber size	真空室尺寸	450 x 370 x 240 mm
Pump Capacity	幫浦能力	德製Oil-filling 21 M3 / hr.
Dimensions	機台尺寸	640 x 530 x 840 mm
Weight	重量	100KG

Model	型號	WSV-600E
Voltage	電壓	220 / 240V
Chamber size	真空室尺寸	48(width) x 30 (depth) x 80 (height) cm
Vacuum Pump	真空幫浦	Oil - Filling 1 HP
Sealing width	封口線寬度	10 mm (Nylon)
Loading weight	荷重	25 KG
Dimension	機器尺寸	83 x 76 x 124 cm

# Band Sealer with Vacuum 連續式抽氣封口機

- Vacuum + Sealing 抽氣+封口
- No Powder & Liquid 不可有粉末及液體
- Optional: Date Coding, Counter 選配: 印字機、計數器
- Distance 35mm from bag mouth to content 袋口預留 35mm

Model	型號	WSY-903A
Voltage	電壓	110 / 220 / 240V 1 phase
Power ( Watt )	瓦特數	1180 W
Sealing & Conveyor speed	速度	1-10M/per min.
Sealing width	封口線寬度	10 mm (Nylon)
Conveyor height adj.	輸送帶調整	90 mm
Loading weight	輸送帶荷重	5 kg/per package
Dimension	機器尺寸	125 x 55 x 110 cm



Nozzle Type 吸嘴式